

of Transportation

Research and Special Programs Administration

400 Seventh Street, S.W. Washington, D.C. 20590

DOT-E 8458 (FIFTH REVISION)

EXPIRATION DATE: February 28, 2002

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. **GRANTEE:** E.I. DuPont de Nemours and Company, Inc. Wilmington, DE

(See Appendix A to this document for a list of additional grantees)

- 2. PURPOSE AND LIMITATION: This exemption authorizes the use of converted DOT specification tank cars with extended retest periods for the transportation in commerce of certain Class 8 hazardous materials and provides no relief from any Hazardous Materials Regulation (HMR) other than as specifically stated.
- 3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
- 4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR \$\$ 173.242; 173.243; 173.29(a); 180.509(c)(3)(ii); 180.509(1)(2).
- 5. This exemption is based on E.I. DuPont de Nemours and Company, Incorporated's application of March 30, 1999, submitted in accordance with § 107.109.

Page 2

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication number	Packing Group
Fluorosulfonic acid	8	UN 1777	I
Nitrating acid mixtures with not more than 50 percent nitric acid	8	UN 1796	II
Nitrating acid mixtures with more than 50 percent nitric acid	8	UN 1796	I
Nitrating acid mixtures spent with not more than 50 percent nitric acid	8	UN 1826	II
Nitrating acid mixtures spent with more than 50 percent nitric acid	σο	UN 1826	I
Sulfuric acid	8	UN 1830	II
Sulfuric acid, spent	8	UN 1832	II
Sulfuric acid, fuming with less than 30 percent free sulfur trioxide	8	UN 1831	I

7. PACKAGING(S) and SAFETY CONTROL MEASURES:

- a. <u>PACKAGING</u> Packaging prescribed are DOT Specification 111A100W2 tank cars converted from either a DOT 105A500W tank car with a 7/8 inch head and shell thickness or a DOT 112A400W tank car with a 3/4 inch head and shell thickness. The upper 2/3 of the tank car must be painted white. Each tank car must be equipped with stainless steel fittings, manway cover and rings and bolted fill hole closures.
- b. <u>TESTING</u> Tank cars operating under the terms of this exemption must be retested under the following schedule:

Retest Intervals in Years			Retest Pressure (psig)			
Tank In	ank Interior and heater Safety systems Relief		Tank	Safety Relief Valves		
Up to	Over 10 to 22	Over 22	Valve		Start to Discharge	Vapor Tight
10	10	10	_ 5	100	75	60

Continuation DOT-E 8458 (5th Rev.)

8. SPECIAL PROVISIONS:

- a. A person who is not a holder of this exemption who receives a package covered by this exemption may reoffer it for transportation provided no modifications or changes are made to the package and it is reoffered for transportation in conformance with this exemption and the HMR.
- b. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation
- c. MARKING Tank cars operating under the terms of this exemption must be marked DOT-E 8458 in four inch letters and numerals on a contrasting background above the DOT specification number.
- 9. MODES OF TRANSPORTATION AUTHORIZED: Rail freight.
- 10. MODAL REQUIREMENTS: The Federal Railroad Administration is to be notified if any unusual incident occurs during the movement by contacting the:

Federal Railroad Administration Office of Safety, Assurance & Compliance, RRS-12 1120 Vermont Avenue, NW, Stop 25 Washington, D.C. 20590 (202) 493-6247 or 493-6229

- 11. <u>COMPLIANCE:</u> Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
 - All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 49 CFR 171-180.
 - Registration required by \$ 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

Continuation DOT-E 8458 (5th Rev.)

Page 4

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

REPORTING REQUIREMENTS. The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must also inform the AAHMS, in writing, as soon as practicable of any incidents involving the package and shipments made under this exemption.

Issued at Washington, D.C.:

MAK 8 4000

(DATE)

Robert A. McGuire

Acting Associate Administrator for

Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590, Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, S.W., Washington, DC 20590-0001, Attention: Records Center, 202-366-5046.

Dist: FRA PO: alb

Continuation DOT-E 8458 (5th Rev.) APPENDIX A JUL 11 200) Page 5

The following are hereby granted party status to this exemption based on their application(s) submitted in accordance with \$ 107.107 or \$ 107.109, as appropriate:

Company Name City/State	Application Date	Issue Date	Expiration Date
NorFalco Sales, Inc., Mississauga, Ontario Canada (U.S. Agent: NorFalco LLC, Independence, OH)	6/8/01	JUL 1 1 2001	2/28/02
Norfalco LLC Independence, OH	6/8/01	JUL 1 1 2001	2/28/02
Noranda-DuPont LLC Wilmington, DE	3/30/99	3/8/00	2/28/02

Robert A. McGuire

Associate Administrator for Hazardous Materials Safety